

AMBERCOMPOSITES

DTR75

Product Description

Premier DTR75 is a pressure-sensitive rubber resin adhesive designed for bonding to "difficult" substrates, such as polyethylene & polypropylene. It can not be used in combination with plasticised PVC.

DTR75 is clean, economical and easy to use straight from the roll or in block form.

Typical Applications

- Joining polythene sheeting
- Bonding kickplates
- Bonding wires to road surfaces
- Fixing carpets
- Mounting lightweight items
- Making products self-adhesive

Technical Information

| | |
|-------------------------|---|
| Adhesive | Rubber resin |
| Tolerances | Thickness & width <10% |
| Colour | Transparent |
| Static shear | No movement allowed 250g/25mmx25mm@20°C |
| Tensile strength | 550 kPa |
| Elongation | >1000% |
| Service temperature | -10°C - +40°C |
| Application temperature | Above 10°C |
| UV resistance | Poor |
| Durability | 10 years + |
| Chemical resistance | Chemicals, oil & petrol will affect the product |
| Shelf life | 1 year |

Please note : The above technical information is given as a guide and is based on recent test data obtained under laboratory conditions. Materials should be fully tested by the end user to establish suitability of the product for the intended application. February 1997

Supplied by

AMBERCOMPOSITES

94 Station Road, Langley Mill
Nottingham, NG16 4BP United Kingdom
T: +44 (0)1773 530899 F: +44 (0)1773 768687
E: sales@ambercomposites.com
www.ambercomposites.com