



EL42

High Temperature Laminating Resin

Three part epoxy laminating resin to be used in conjunction with Amber Composites HX42 Low temperature curing Epoxy Prepreg.

FEATURES: High end-use temperature (190°C)

APPLICATIONS: 1) Laminating backing structures
2) Coupling coats (If Amber EG42 gel coat applied)

MIX RATIO	PART A	PART B	PART C
Colour	Amber	Pink	Blue
p.b.w	100	56	2

PACKAGING: Part A 5.0 kg
Part B 2.8 kg
Part C 120 g

STORAGE: Store at below 15°C in dry conditions. Shelf life of constituent components: 12 months at < 15°C

HANDLING SAFETY

Observe established precautions for handling epoxy resins and solvents. Wear gloves and use suitable breathing masks, preferably air fed.

For further information refer to Material Safety Data Sheet.

FURTHER INFORMATION

Please contact Amber Composites for additional information.

This is not a specification. The information given in this data sheet in relation to the performance, storage and other characteristics of the product is based on results gained from experience and tests and is believed to be accurate. Given, however, that conditions of use and storage will vary, Amber Composites will not be liable for any loss or damage resulting from reliance upon such information. The purchaser is recommended to carry out his own tests to establish the suitability of the product for its particular purpose. The use of the product in certain processes may require third party consent.