



SURFACE ACTIVATOR

Revision: 19/07/2005

Page 1 of 1

Technical Data:

Base	Mixture of solvents and adhesion promoters
Consistency	Liquid
Specific Gravity	1,0 g/mL

Product:

Surface Activator is at the same time a cleaner, degreaser and primer. It will activate non porous surfaces to achieve an improved adhesion.

Applications:

Cleaning, degreasing and activating of non porous substrates
Not suited as a stand alone cleaning agent

Packaging:

Colour: transparent
Packaging: tin 500mL

Shelflife:

6 months in unopened packaging in a cool and dry storage place at temperatures between +5°C and +25°.

Surfaces:

Type: all non porous surfaces
We recommend a preliminary compatibility test.

Application:

Method: apply with a cloth. Wipe surfaces allways in the same direction. Replace cloth regularly when dirty. Leave to evaporate for ca. 5 minutes. Apply sealant/adhesive immediately after evaporation.

Remarks:

Do not use on porous surfaces like wooden constructions.

Remark: The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. In every case it is recommended to carry out preliminary experiments.