



## VACtiteUltraP

Pink, nylon vacuum bagging film

### Production Description

Pink, nylon vacuum bagging film  
(lay-flat tube) – roll length 150 linear metre

### General Description

A strong and supple, mono-layer, heat stabilized nylon bagging film for oven and autoclave processing.  
Supplied as a lay-flat tubular film

### Colour

Pink

### TECHNICAL DATA

	<u>Metric</u>	<u>IMPERIAL</u>
<b>Nominal Yield:</b>	8.77 m <sup>2</sup> / Kg (for 0.050 mm)	6,175 sq. in./lb (for 0.002")
<b>Tensile Strength at Yield:</b>	8300 N / cm <sup>2</sup>	11,900 psi
<b>Elongation at Fail, % :</b>	190	190
<b>Elongation at Yield, %:</b>	9	9
<b>Secant Modulus:</b>	303,400 N / cm <sup>2</sup>	435,000 psi
<b>Melting point (DSC)</b>	215°C	420°F
<b>Deflection Temperature</b>	205°C (at 46 N / cm <sup>2</sup> ) 71°C (at 184 N / cm <sup>2</sup> )	400°F (at 66 psi) 160°F (at 264 psi)
<b>Specific Gravity:</b>	1.14	1.14
<b>Maximum Usage Temperature:</b>	205°C	400°F

### FURTHER INFORMATION - PROCESSING DETAILS

Please contact Amber Composites for further information.

This is not a specification. The information given in this data sheet in relation to the performance, storage and other characteristics of the product is based on results gained from experience and tests and is believed to be accurate. Given, however, that conditions of use and storage will vary, Amber Composites will not be liable for any loss or damage resulting from reliance upon such information. The purchaser is recommended to carry out his own tests to establish the suitability of the product for its particular purpose. The use of the product in certain processes may require third party consent.